

# PERMA FLEX 3

---

## RAPID HARDENING CRACK AND JOINT FILLER

**CAUTIONARY INFORMATION: DO NOT USE THIS PRODUCT BEFORE READING THE MATERIAL SAFETY DATA SHEET. FOR INDUSTRIAL/PROFESSIONAL USE ONLY. DO NOT TRANSFER TO UNMARKED CONTAINERS. KEEP OUT OF REACH OF CHILDREN**

THE ONE GALLON CAN OF PERMA FLEX 3 LIQUID INCLUDED IN THIS UNIT CONTAINS STYRENE AND UNTIL IT IS MIXED WITH POWDER AND HAS CURED, THE FOLLOWING SAFETY PRECAUTIONS SHOULD BE FOLLOWED.

**CAUTION! FLAMMABLE LIQUID:** KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAME. NO SMOKING

**WARNING: HARMFUL IF INHALED OR SWALLOWED.**

MAY CAUSE IRRITATION OF SKIN, EYES, NOSE OR THROAT. AVOID CONTACT WITH EYES, SKIN OR CLOTHING. AVOID BREATHING VAPOR. USE ONLY WITH ADEQUATE VENTILATION. KEEP CONTAINER CLOSED WHEN NOT IN USE. WASH HANDS AFTER HANDLING. WASH CLOTHING BEFORE RE-USE. DO NOT TRANSFER CONTENTS TO BOTTLES OR OTHER UNLABELED CONTAINERS. **KEEP OUT OF REACH OF CHILDREN!**

**FIRST AID:** ON CONTACT, FLUSH EYES OR SKIN WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. REMOVE CONTAMINATED SHOES AND CLOTHING. IF NOT BREATHING GIVE ARTIFICIAL RESPIRATION AND/OR ADMINISTER OXYGEN. IF SWALLOWED, INDUCE VOMITING.

**CALL A PHYSICIAN.**

**SURFACE PREPARATION:** SAWCUT MUST BE CLEAN AND FREE OF ANY FILM, DUST, GREASE AND OIL. FOREIGN MATTER/ LAITANCE MUST BE BLOWN OUT, USING OIL FREE COMPRESSED AIR.

**MIXING DIRECTIONS & APPLICATION:** FOR A LEVEL CRACK : POUR A QUANTITY (HALF A GALLON IS RECOMMENDED) OF THE LIQUID INTO A CLEAN CONTAINER, PREFERABLY PLASTIC. GRADUALLY ADD THE POWDER (APPROXIMATELY 7.5 POUNDS) TO THE LIQUID STIRRING CONSTANTLY UNTIL A UNIFORM CONSISTENCY IS ACHIEVED (SIMILAR TO PANCAKE BATTER). MECHANICAL MIXING PREFERABLE

**FOR A CRACK ON A GRADE:** FOLLOW THE SAME DIRECTIONS AS ABOVE EXCEPT ADD SLIGHTLY MORE POWDER TO MAKE A STIFFER MIX TO PREVENT THE SEALANT FROM FLOWING OUT THE BOTTOM OF THE SAWCUT.

DO NOT ADD ANYTHING TO PERMA FLEX 3.

DO NOT MIX MORE THAN BE USED WITHIN THE POT LIFE OF THE MATERIAL, WHICH IS 10 MINUTES

WHEN APPLYING PERMA FLEX 3, ALLOW THE MATERIAL TO FLOW SLOWLY INTO THE CRACK OR SAWCUT AND SETTLE AND SELF LEVEL. PERMA FLEX 3 MAY BE APPLIED TO DAMP SURFACES AND CAN BE APPLIED TO SURFACES BELOW 32 DEGREES.

AS A RUNWAY LIGHT GROUT - MIX TO A FLOWABLE CONSISTENCY TO USE.

**NOTE:** SAVE ANY EXTRA POWDER, AS PERMA FLEX 3 LIQUIDS MAY BE PURCHASED SEPARATELY.

**COVERAGE:** 50-75 LINEAR FEET PER KIT (MAXIMUM 2 GALLON YIELD) DEPENDING ON WIDTH/DEPTH OF CRACK OR JOINT.

**SHELF-LIFE STABILITY:** APPROXIMATELY 9-12 MONTHS. FOR EXTENDED SHELF LIFE, STORE AT TEMPERATURES BELOW 80 DEGREES F. AND KEEP LIQUID RESIN SECURELY CLOSED WHEN NOT IN USE.

**CLEAN UP:** USE TOPSOLV 100 MANUFACTURED BY E.L.S. PRODUCTS CORP

**CAUTION: WARNING!!** HARMFUL IF INHALED OR SWALLOWED. MAY CAUSE IRRITATION OF SKIN, EYE, NOSE OR THROAT.

**FLAMMABLE:** KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAME. USE WITH ADEQUATE VENTILATION

RECOMMENDATIONS FOR THE USE OF THIS PRODUCT ARE BASED ON RELIABLE TESTS. NO GUARANTEE OF RESULTS ARE IMPLIED WHERE CONDITIONS ARE BEYOND OUR CONTROL. UNDER NO CIRCUMSTANCES OR CONDITIONS, EITHER EXPRESSED OR IMPLIED WILL E.L.S. BE LIABLE FOR DAMAGES IN EXCESS OF THE PURCHASE PRICE OF THIS PRODUCT.

10-55



**E.L.S. Products Corp.**

**1.800.528.4861**